


REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 26, 1995		3. REPORT TYPE AND DATES COVERED Final 15 Jun 93 - 31 Mar 95
4. TITLE AND SUBTITLE Novel Sources for the Far-Infrared Utilizing a 1 MeV Electron Gun			5. FUNDING NUMBERS DAA103-90-G-0188	
6. AUTHOR(S) Charles R. Jones				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) N. C. Central University, Physics Department, P.O. Box 19708, Durham, NC 27707			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSORING/MONITORING AGENCY REPORT NUMBER ARO 31244.2 PH-SAH	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The use of the compact NCCU electron gun to generate radiation from the microwave region to above one Terahertz has been demonstrated. Several radiation mechanisms were explored, including waveguide excitation, transition radiation, and a grating-coupled device.				
14. SUBJECT TERMS far-infrared, electron gun, Terahertz, transition radiation			15. NUMBER OF PAGES 2	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

19951025 056

DTIC QUALITY INSPECTED 8



Novel Sources for the Far-Infrared Utilizing a 1 MeV Electron Gun

FINAL REPORT

Submitted by: Professor Charles R. Jones

June 26, 1995

U. S. ARMY RESEARCH OFFICE

ARE GRANT DAAL03-90-G-0188

Accession For	
NTIS CRA&I	✓
DTIC TAB	
Unannounced	
Justification	
By _____	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

North Carolina Central University

APPROVED FOR PUBLIC RELEASE
DISTRIBUTION UNLIMITED

Final Report

Over the course of this project the NCCU electron gun was successfully completed and used to conduct a variety of experiments on the generation of radiation in the far-infrared. The first "proof-of-principle" experiments studied the radiation produced when a rectangular waveguide was excited by passing the electron beam transversely across the waveguide. These results have been reported in a paper submitted to Applied Physics Letters.

Observation of strong transition radiation while performing the waveguide experiments led us to look more closely at transition radiation as a tool for generating radiation. Two experiments were conducted and much was learned regarding the adjustment of gun parameters to optimize the electron bunch shape and maximize the radiation generated. The power generated and the spectral coverage obtained has steadily increased. Although accurate power estimates are difficult to obtain, considerably more power was obtained with the transition radiation mechanism than with the initial waveguide experiments. The average power on each harmonic, during the macropulse, is estimated to be greater than a milliwatt over the range from 100 to 1000 GHz. The micropulse length in the time domain is less than a picosecond so this corresponds to a peak power in the micropulse of at least several hundred Watts. Some power is observed up to 4 THz but accurate studies above 1 THz will require improving and purging the spectrometer. A paper is in preparation on the transition radiation experiments to date.

In addition to the waveguide and transition radiation studies, some time was devoted to studying the operation of an orotron device fabricated by researchers from Ohio State University. We found that the device would oscillate on individual harmonics between about 270 and 300 GHz and could be adjusted to operate simultaneously on as many as a two dozen harmonics. Power levels again were estimated to be on the order of milliwatts per harmonic. Further experiments on grating-coupled devices are planned in collaboration with researchers at Duke University, Dartmouth College, and Ohio State University.

Scientific Personnel: Dr. Charles R. Jones, Dr. J. M. Dutta, Dr. H. Kosai
Mr. Robert McDuffie, Mr. George Digsby

Report of Inventions: None